
SPECIFICATIONS

| Dimension | Metric | British |
|---------------------------------|-------------|-----------------|
| Max. Working Height \Lambda | 5.00m | 16ft 5in |
| Max. Platform Height B | 3.00m | 9ft 10in |
| Overall Length 🕞 | 1.31m | 4ft 3in |
| Overall Width | 0.75m | 2ft 5in |
| Overall Height | 1.80m | 5ft 11in |
| Platform Size(Length ×Width) | 1.15m×0.52m | 3ft 9in×1ft 8in |
| Ground Clearance(Stowed/Raised) | 0.08m | 3in |
| Wheelbase 🚯 | 0.99m | 3ft 3in |
| Tyres | φ200×50mm | φ200×50mm |

JCPT0507C

Mobile Scissor Lifts

ELECTRIC





CE EN 280

Max. Occupants(Indoor/Outdoor)1/01/0Max. Working Slope1°1°Up/Down Speed21/21sec21/21sec

240kg

529lb

| Weight | | |
|----------------|-------|-------|
| Overall Weight | 395kg | 871lb |

Power

Performance

S.W.L

| Hydraulic Tank | 3L | 0.8gal |
|-------------------|-------------|-------------|
| Lead-acid Battery | 12V/85Ah | 12V/85Ah |
| Charger | 12V/15A | 12V/15A |
| Lifting Motor | 12VDC/0.8kW | 12VDC/0.8kW |





FEATURES

Standard Items

- Self-lock Gate On Platform
- Fixed Guardrails
- Automatic Brake System
- Emergency Descent System
- Cylinder Holding Valve
- Onboard Diagnostic System
- Tilt Alarm
- All Motion Alarm
- Horn
- Hour Meter
- Safety Arm For Troubleshooting
- Standard Transport Forklift Holes
- Charging Protection System
- Flashing LED Beacon
- Charging Indicator
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- Platform Load Sense System
- Emergency Stop Button



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road,Deqing,Zhejiang P.R.C 313219 Telephone: +86(572)8681688

E-Mail: export@cndingli.com

Https://en.cndingli.com

Due to continuous technology updates, technical parameters are subject to change without notice. This picture book is for reference only, the actual product shall prevail. The copyright is owned by zhejiang dingli, any content may not be copied for any purpose without written permission. 2024-08

